

## **Electrolux Professional Line 5000**

# Electrolux 200 G-force Washers S-Series, Super Spin for Coin/Card

# Save up to 50% on water – automatically. They can even talk and text message you!

Electrolux Professional 200 G-Force high-speed extraction washers minimize drying time and provide significant electrical and gas savings. Self-service laundries benefit from faster throughput (freeing up dryers, folding tables and parking spots) which creates higher profits. Your customers can even receive a text message (optional) notifying them when their wash is done and ready for unloading! Increase your profits and create customers for life with the unique features of Electrolux Professional washers.

#### **FEATURES AND BENEFITS:**

- AS (Automatic Savings) Save up to 50% on water with AS, automatically. With every wash cycle, AS determines the actual weight of the load and adds precisely the right amount of water significantly reducing water consumption and energy costs
- Extremely low water and energy consumption
- Convenient four compartment detergent box
- Large, secure coin box
- · High extraction force removes more water, saving energy & time in dryer
- Heavy-duty construction with robust steel door and lock, hinges set wide apart and door locked through entire wash cycle
- · Stainless and galvanized steel in all vital parts for maximum rust protection
- · SuperBalance guarantees the correct extraction force, longer machine life
- · Sanitizing Rinse for greater customer satisfaction and additional revenue
- Single phase electrical for easy installation & lower costs
- Drain pump option
- Text messaging option
- Voice guidance option

#### **COMPASS PRO MICROPROCESSOR OFFERS:**

- · Easy to customize programs
- Large display and one control knob for easy program selection
- More than 20 languages available displays two languages, simultaneously
- Real time clock for time of day pricing, happy hour pricing and promotions
- Heavy Soil and Extra Rinse option buttons for higher customer satisfaction
  and increased revenue
- · Detailed user statistics and programmability



Designed by experts. Inspired by you.





Available in 20, 25, 30, 45, 62 & 77 lb. capacities. Vertical blue wave front panel standard. Stainless available. Most sizes available in 220 or 120 volt, single phase.

Electrolux models are designed to save water and energy and achieve impressive Modified Energy Factor (MEF) results.



For more information, please visit www.laundrylux.com

	Hts through 36° door!											
Electrolux "S"Models, 200G Washers	W585S		W5105S		W5130S		W5180S		W5250S		W5330S	
Capacity (lb/kg)	20	9	25	11	30	14	45	20	62	28	77	35
Width (in/mm)	26	660	28 3/8	720	28 3/8	720	29 1/2	750	32 11/16	830	35 13/16	910
Depth (overall) (in/mm)	28 7/16	722	27 7/16	697	31	787	36	914	40 1/2	1029	43 7/8	1114
Height (in/mm)	44 5/8	1133	47 15/16	1217	47 7/8	1216	52 15/16	1345	56 1/8	1426	57 11/16	1465
Height to bottom of door (in/mm)	14	355	14 3/8	365	14 3/8	365	17 1/8	435	18 1/2	470	19 11/16	500
Door opening diameter (in/mm)	12 1/4	310	14 3/8	365	14 3/8	365	15 9/16	395	17 1/8	435	17 1/8	435
Cylinder volume (ft3/l)	3	85	3.7	105	4.6	130	6.4	180	8.8	250	11.7	330
Drain outlet diameter (in/mm)	3	75	3	75	3	75	3	75	3	75	3	75
Height to centerline of drain (in/mm)	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103	4 1/16	103
Extract (rpm/G-Force)	830 / 200		776 / 200		776 / 200		742 / 200		702 / 200		641 / 200	
Dynamic floor load (lb/kN)	382 +/- 585	1.7 +/ -2.6	427 +/- 674	1.9 +/- 3	517 +/- 854	2.3 +/- 3.8	674 +/- 1079	3 +/- 4.8	854 +/- 1326	3.8 +/- 5.9	967 +/- 1551	4.3 +/- 6.9
Dynamic frequency (Hz)	13.8		12.9		12.9		12.4		11.7		11.2	
Noise level (dBA) in extraction	<75		<71		<72		<74		<76		<75	
Crated width - (in/mm)	27 3/16	690	29 1/2	750	29 1/2	750	30 11/16	780	33 7/8	860	37	940
Crated depth - (in/mm)	32 11/16	830	35 1/16	890	37 3/8	950	39 3/16	995	43 11/16	1110	47 1/16	1195
Crated height - (in/mm)	48	1219	53 1/8	1350	53 1/8	1350	56 7/16	1434	61 1/4	1556	62 7/16	1586
Crated weight (lb/kg)	276	126	364	166	370	169	522	238	615	280	717	326
Electrical Requirements (standard)												
Voltage/frequency/phase	208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~		208-240/60/1 or 3~	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.5 / 2.4 / 15		0.7 / 3.4 / 15		0.8/3.9/15		0.9/4.3/15		1.1 / 5.3 / 15		1.2 / 5.8 / 15	
Voltage/frequency/phase	120/60/1		120/60/1		120/60/1		120/60/1		120/60/1		120/60/1	
Power (kW) / Full-load current (A) / Ckt breaker (A)	0.6 / 5.0 / 15		0.8 / 5.8 / 15		0.9 / 7.5 / 15		1.0 / 8.3 / 15		1.2 / 10.0 / 15		1.3 / 10.8 / 15	
Water Information												
Inlet fittings (* = 3 inlets)	3/4	DN20	3/4	DN20	3/4	DN20	3/4*	DN20*	3/4*	DN20*	3/4*	DN20*
Flow (gpm/lpm @ 45 psi) (each inlet)	5	20	5	20	5	20	5	20	16	60	16	60
Recommended water pressure (psi/kPa)	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600	30-90	200-600
Approx Water usage (gal / liters @ full load)	10.8	41	14.3	54	16.5	62	23.7	90	32.7	124	43.5	165
Modified Energy Factor	2.1		2.1		2.2		2.3		2.0		2.0	
Water Factor (Gal per cycle/drum volume)	4.0		3.9		3.9		4.0		4.0		4.0	

Refer installation and servicing to qualified, licensed personnel. Always read installation and operating manuals and consult local codes before installation. Protect machines with properly rated, common-trip, circuit breakers ONLY. Warranty void if not properly installed. Solid-mount machines require a concrete foundation, and are not suitable for upper-floor or above-basement installations. Contact us for more information and for availability of machines for electric services not listed. Specifications subject to change without notice. Laundrylux assumes no responsibility for errors or omissions in this information.

## Electrolux Professional Line 5000 The all-in-one business solution for your self-service laundry.



**Greatest flexibility** with Compass Pro\*

- Real-time clock for time-of-day and happy hour pricing
- Multi-language menu selection
- Easy to customize
- Simple to use
- Revenue generating option
  buttons



Extended lifetime due to Super Balance / Power Balance<sup>™</sup>

- Lower maintenance costs
- Less vibration
- Maximum water extraction
- Lower energy costs



### Cost savings in water & energy

ÆD

with Automatic Savings (AS)

Fits through 36" do

- Determines load weight and adds precisely the correct amount of water
- Up to 50% water savings automatically
- Reduces water and energy consumption

Please contact your local authorized Electrolux Professional Distributor.

For Electrolux Professional Laundry Solutions in North America:

### Laundrylux 800.381.7222 • laundrylux.com

Laundrylux • 461 Doughty Blvd., Inwood, NY 11096-0338 T 516-371-4400 • F 516-371-4204 • sales@laundrylux.com **Parts:** 516-371-2000 • F 516-371-4029 • parts@laundrylux.com **Technical Care:** 516-371-0700 • F 516-371-4029 • techcare@laundrylux.com **En Mexico:** Llame gratis a este numero 001-800-010-1010

